


Spina Chevron 45° Rovere Oak



Spina Ungherese 45° Chevron 45°



CARATTERISTICHE

- Supporto in multistrato
- Incastro maschio e femmina su 4 lati
- Primo strato di legno nobile 3-4mm
- Angoli Bisellati
- Posa incollata

L'umidità ambientale d'esercizio deve essere compresa tra il 45% ed il 60% ad una temperatura di circa 20°C.

N.B.

Il legno è un materiale naturale, ogni tavola è un esemplare unico, per questo motivo più tavole possono differire tra loro nel colore.

—

Si sconsiglia l'uso di nastro adesivo sulle finiture artigianali in quanto può danneggiare la superficie.

CHARACTERISTICS

- Plywood support
- Tongue and groove on 4 sides
- Top layer prestigious wood 3-4mm
- Bevelled Edges
- Glued installation

The operating environmental humidity must be between 45% and 60% at a temperature of approximately 20°C.

Please note:

Wood is a natural product and each plank is a unique specimen, hence planks may differ one from the other in colour.

—

The use of adhesive tape on the handcrafted finishes is not recommended as it can damage the surface.




Parquet multistrato 1strip
Engineered wood flooring 1strip



P01
Prelevigato bisellato
Unfinished beveled



Finiture standard come
Standard finishing as
Dimora



U11 Vernice OIL UV

Dimora*
11x140x500/700mm
CLASSIC
FREE

Dimora*
11x140x500/700mm
CLASSIC
FREE

Decora*
15x135/185x600/1000mm
CLASSIC
FREE

Decora*
15x135/185x600/1000mm
CLASSIC
FREE

Decora Thermo
15x90x600mm
CLASSIC
FREE

Decora Thermo
15x90x600mm
CLASSIC
FREE

Masseria
14x90x510-600mm
14x125x785mm
VENERE

Masseria
14x90x510-600mm
14x125x785mm
VENERE

Masseria
14x90x510-600mm
14x125x785mm
VENERE

*SU DIMORA E DECORA SI PUÒ AVERE ANGOLO A 60°
*ON DIMORA AND DECORA AVAILABLE ALSO CHEVRON 60°

FINITURE ARTIGIANALI SUL PRODOTTO PRELEVIGATO
CUSTOMIZED FINISHES ON PRESANDED PRODUCT