

STONE PLASTIC COMPOSITE - SPC

i.Cov / 5.5 Fast Click Plus - Plank

Product type	EN ISO 10582	Heterogeneous Poly (vinyl chloride) floor coverings
Classification	EN ISO 10874	Domestic 23-commercial 33

CHARACTERISTICS

Total thickness	EN ISO 24346	6 mm (4,5+1,5mm Insulating sheath)
Wear Layer thickness	EN ISO 24340	0,55 mm
Sizes	EN ISO 24348	1524 x 228 mm
Packaging		6 pieces / pack equal to 2,085 m ²
Weight		10 kg / m ²
Square edge		YES

TECHNICAL PERFORMANCE

Reaction to fire	EN 13501-1	Bfl-s1
Castor chair effect	EN ISO 4918	No Damage
Furniture legs	EN 424	Not affected
Chemical resistance	EN ISO 26987	Resistant
Thermal resistance	EN ISO 10156	0,046 m2 K/W
Floor heating		Suitable Max 27°C
Slip resistance	DIN 51130	R10 angle 15.6°
Improvement of impact sound insulation	DIN EN ISO 717-2	19 dB



EN 14041 : 2004



**Click
Automatico**



**100%
WATERPROOF**

IMPORTANT NOTICE

This message, for the law 196/2003, may contain confidential and/or privileged information. If you are not the address or authorized to receive this message or any information herein. If you have received this message in error, please advise the sender immediately by replay e-mail and delete this message. Thank for your cooperation.